



COUNTY OF LOS ANGELES
DEPARTMENT OF PUBLIC WORKS
"To Enrich Lives Through Effective and Caring Service"

BUILDING AND SAFETY DIVISION

900 SOUTH FREMONT AVENUE
 ALHAMBRA, CALIFORNIA 91803-1331
 Telephone: (626) 458-3173
<http://dpw.lacounty.gov/bsd>

TABLE 4.504.1/TABLE 5.504.4.1 ADHESIVE VOC LIMIT^{1,2} Grams of VOC per Liter of Coating, Less Water and Less Exempt Compounds	
ARCHITECTURAL APPLICATIONS	VOC LIMIT
Indoor carpet adhesives	50
Carpet pad adhesives	50
Outdoor carpet pad adhesives	150
Wood flooring adhesives	100
Rubber floor adhesives	60
Subfloor adhesives	50
Ceramic tile adhesives	65
VCT and asphalt tile adhesives	50
Drywall and panel adhesives	50
Cove base adhesives	50
Multipurpose construction adhesives	70
Structural glazing adhesives	100
Single-ply roof membrane adhesives	250
Other adhesives	50
SPECIALITY APPLICATIONS	
PVC welding	510
CPVC welding	490
ABS welding	325
Plastic cement welding	250
Adhesive primer for plastic	550
Contact adhesive	80
Special purpose contact adhesive	250
Structural wood member adhesive	140
Top and trim adhesive	250
SUBSTRATE SPECIFIC APPLICATIONS	
Metal to metal	30
Plastic foams	50
Porous material (except wood)	50
Wood	30
Fiberglass	80
1.	If an adhesive is used to bond dissimilar substrates together, the adhesive with the highest VOC content shall be allowed.
2.	For additional information regarding methods to measure the VOC content specified in this table, see South Coast Air Quality Management District Rule 1168